

Type of product	Capacity, kW	Voltage, V	Rotational speed, rpm	Efficiency, %	Weight, kg
1500 rpm					
DAZO4-560X-4DN1	1000	10000	1500	95,00	4520
DAZO4-560X-4N1	1250	6000	1500	95,50	4840
DAZO4-560Yk-4DN1	1250	10000	1500	95,30	5200
DAZO4-560Yk-4N1	1600	6000	1500	95,80	5570
DAZO4-560Y-4DN1	1600	10000	1500	95,60	5580
DAZO4-560Y-4N1	2000	6000	1500	96,00	6040
1000 rpm					
DAZO4-560X-6DN1	800	10000	1000	94,90	4610
DAZO4-560X-6N1	1000	6000	1000	95,50	4930
DAZO4-560Yk-6DN1	1000	10000	1000	95,20	5310
DAZO4-560Yk-6N1	1250	6000	1000	95,80	5630
DAZO4-560Y-6DN1	1250	10000	1000	95,50	5670
DAZO4-560Y-6N1	1600	6000	1000	96,00	6140
750 rpm					
DAZO4M-560X-8DN1	630	10000	750	94,40	5785
DAZO4M-560X-8N1	630	6000	750	94,70	5875
DAZO4M-560Yk-8DN1	800	10000	750	94,70	6275
DAZO4M-560Yk-8N1	800	6000	750	95,00	6325
DAZO4M-560Y-8DN1	1000	10000	750	95,00	6660
DAZO4M-560Y-8N1	1000	6000	750	95,30	6690

Type of product	Capacity, kW	Voltage, V	Rotational speed, rpm	Efficiency, %	Weight, kg
600 rpm					
DAZO4-560Xk-10N1 (with 2 terminal boxes)	400	3000	600	94,77	4200
DAZO4-560Xk-10N1	400	6000	600	93,60	4200
DAZO4-560X-10N1	500	6000	600	94,10	4500
DAZO4-560X-10DN1	500	10000	600	93,80	4510
DAZO4-560Yk-10N1	630	6000	600	94,60	5260
DAZO4-560Yk-10DN1	630	10000	600	94,30	5280
DAZO4-560Y-10N1	800	6000	600	94,90	5620
DAZO4-560Y-10DN1	800	10000	600	94,60	5650
500 rpm					
DAZO4-560Xk-12N1	315	6000	500	92,90	4200
DAZO4-560X-12N1	400	6000	500	93,40	4500
DAZO4-560X-12DN1	400	10000	500	93,10	4500
DAZO4-560Yk-12N1	500	6000	500	93,90	5250
DAZO4-560Yk-12DN1	500	10000	500	93,60	5260
DAZO4-560Y-12N1	630	6000	500	94,40	5600
DAZO4-560Y-12DN1	630	10000	500	94,10	5610
DAZO-M-560-79-6N1* (to drive mills)	1000	6000	1000	95,10	6700

Note: * 79 – length of stator core, cm

Symbolic notation structure:

