

Type of product	Capacity, kW	Voltage, V	Rotational speed, rpm	Efficiency, %	Weight, kg
SDK2					
SDK2-16-24-12CNF4	315	6000 10000	500	92,3 91,9	2460 2470
SDK2-16-29-12CT4	315	6000 3000	500	92,7	2750
SDK2-16-29-14C NF4 (T4) 60 Hz	320	6000 3000	514	93,0	3130
SDK2-16-29-12C T4 60 Hz	400	6000	600	93,1	2750
SDK2-16-24-10C NF4	400	6000 10000	600	93,9	2550 2670
SDK2-16-24-10CT4	400	6000	600	93,5	2560
SDKS-16-29-12FNF4	400	6000	500	94,0	4100
SDK2-16-36-12C NF4	500	6000	500	93,7	3250
SDK2-17-26-12C NF4	630	3000 6000 10000	500	93,7 94,5 94,5	3600 3600 3640
SDK2-17-26-12C T4	630	3000 6000 6600	500	94,1	3550
SDK2-17-26-16C NF4	500	6000	375	93,5	3900
SDK2-17-29-14C NF4 (T4) 60 Hz	630	3000 6000	514	94,3	4030
SDK2-16-44-10C NF4	630	10000	600	95,0	3780
SDK2-16-44-10C T4	710	6000	600	95,3	3800
SDK2-16-44-10C NF4	800	6000	600	96,0	3770
SDK2-17-39-12F NF4	1000	6000 10000	500	95,0 94,0	5930 5550

DSK					
DSK 173/16-16A NF4	315	6000	375	92,0	3220
DSK-315-500-6M NF4	315	6000	500	92,0	2460
DSK-315-500-10M NF4	315	10000	500	92,0	2410
DSK-400-600-6M NF4	400	6000	600	94,0	2544
DSK-400-600-10M NF4	400	10000	600	95,0	2630
DSK-630-500-6M NF4	630	6000	500	94,5	3400
DSK-630-500-10M NF4	630	10000	500	94,5	3420
DSK-710-600-6M NF4 (T4)	710	6000	600	95,3	3824

Symbolic notation structure:

