

✓ Converter Gas Coolers (Ferrous Metallurgy).
Vertical water-tube single-drum steam generators.

Boiler type	Steaming capacity	Pressure	Steam temperature	Gas flow rate	Gas inlet/outlet temperature	Gas duct cross-section	Boiler metal weight	Remarks
	t/hr	MPa	°C	Nm ³ /hr	°C	m	t	
OKG-250-2	250	4,0	249	168000	1600/ 780	3,42 x 3,42	520	Tower-type boiler; multiple forced circulation
OKG-400	370			330000	1650/1070	4,8 x 4,85	660	U-shaped arrangement; multiple forced circulation
OKG-400-2M	347			250000	1620/740	4,2 x 4,25	642	U-shaped arrangement; combined circulation
OKG-130	345			80000	1700/750	4,2 x 4,25	605	U-shaped arrangement; multiple forced circulation
OKG-130 BD-1	345			186000	1650/750	4,2 x 4,25	620	
OKG-130 BD	345							
OKG-160U	260			4,0	249	60000	1700/724	3,6 x 3,65
OKG-160 BD-1	200	90000 ÷ 115000	1700/500			410		
OKG-160U-2	275	60000	1700/600			4,2 x 4,25	550	
OKG-300-1	200	2,4	221	190000	1700/950	∅3,9 (polyhedron)	400	U-shaped arrangement; multiple forced circulation